

# STT

P/L/A/T/F/O/R/M T/R/U/C/K & T/O/W T/R/A/C/T/O/R



- Small, but it has powerful towing capacity
- Tight turning radius for increased mobility in narrow places
- Suitable for towing trailers and bulky cargos in manufacturing and warehousing

# Platform Truck & Tow Tractor

Total Moving System SOOSUNG



## Specifications

Model	STT-2000		SCT-2000	
	Metric	British unit	Metric	British unit
Towing Capacity	kg lbs	2000 4409 lbs	2000	4409 lbs
Lifted Drawbar Height	mm inch	325 12.8"	325	12.8"
Lowered Drawbar Height	mm inch	200 7.9"	200	7.9"
Overall Length	mm inch	1339 52.7"	1464	57.6"
Overall Width	mm inch	750 29.5"	750	29.5"
Overall Height	mm inch	1390 54.7"	1390	54.7"
Drawbar	mm inch	Ø 30x60mm Ø 12" x 27"	Ø 30x60mm	Ø 12" x 27"
Turning Radius		1120 44.1"	1400	55.1"
Travel Speed	With Load km/hr		4~5	
	Without Load km/hr		5~6	
Motor	Drive Mtor kw		24V x 1.1kw	
	Hydraulic Mtor kw		24V x 2kw	
Battery		24V x 170Ah/5h		
Battery Charger		Ac 1φ x 220V, 50Hz		

※ The above specifications are subject to change without prior notice.

■ Option : Ride Type (SCT-2000)



 SOOSUNG LIFT MFG. CO., LTD.


123 Block 4 Lot, No.61 Namdong-Ro, Namdong-Gu, Incheon, 405-820, Korea  
TEL : 82-32-818-5160, FAX : 82-32-818-7513

e-mail : [soosung@soosung.com](mailto:soosung@soosung.com)  
website : [www.soosung.com](http://www.soosung.com)

기획·제작 : (주)엑스컴(www.ek.com) T.02)8141-7336 www.ek.com.co.kr 0510

 SOOSUNG LIFT MFG. CO., LTD.

Korea



# SPT - 1500

The SPT platform truck and SST tow tractor are ideal choices wherever large quantities of goods have to be moved. Soo sung tractors can transport goods from one point to another with ease.



■ SPT-1500 (3-wheel)

# SST- 2000N 4000



P/L/A/T/F/O/R/M T/R/U/C/K & T/O/W T/R/A/C/T/O/R



■ SST-4000 (3-wheel)



■ SST-2000N (4-wheel)

## Specifications

Model		SPT-1500		Option		
Metric	British unit					
Load Capacity	kg lbs	1500	3307 lbs			
Length	mm inch	1400	55.1"			
Cargo Deck	mm inch	1100	43.3"			
Height	mm inch	600	23.6"			
Overall Length	mm inch	2780	109.4"			
Overall Width	mm inch	1100	43.3"			
Overall Height	mm inch	1400	55.12"			
Weight (incl. Battery)	kg lbs	1150	2535 lbs			
Travel Speed	With Load km/hr	6				
	Without Load km/hr	9				
Tire	Front mm inch	Ø 343 x 140 (1)				
	Rear mm inch	5.00-8(2)				
Battery	48V x 201Ah/5Hr					
Battery Charger	AC 3Ø x 380V/220V, 50Hz					
Drive Motor	48V x 4kw					

※The above specifications are subject to change without prior notice.

- Electric-powered, multi-purpose cargo cart with driver seat
- Suitable for cargo handling at factories, distribution centers, supermarkets, warehouses, freight terminals and airports.

Cargo Deck Size  
Cargo Deck Gate



### Battery Charger

- Automatically recharges to optimal levels while unit is connected to a power source
- Automatic voltage checking system avoids overcharging, extending the battery life.



### Speed Controller

Using a micro-processor and by adopting a digital control method and a highly integrated power module technology, Soosung has designed its own DC motor speed controller. The result is a small and compact speed control that prevents sudden accidental starts, and a self diagnostic/protective function, yet with a robust variable speed controller.

## Specifications

Model		SST-2000N 4-wheel		SST-4000 3-wheel	
Towing Capacity		kg lbs	2000 4409 lbs	4000 8818 lbs	
Travel Speed	With Load	km/hr	8	6	
	Without Load	km/hr	18	10	
Overall Length	mm inch	2080	81.8"	2070	81.5"
Overall Width	mm inch	1050	41.3"	1100	43.3"
Overall Height	mm inch	1750	68.8"	1330	52.4"
Wheel Base	mm inch	1650	64.9"	1225	48.2"
Turning Radius		2400	94.5"	1920	75.6"
Weight (incl. Battery)	kg lbs	415	915 lbs	1130	2491 lbs
Drive Motor	kw	4	4		
Battery	Voltage	DC48V	DC48V		
	Capacity	150A/20Hr	201A/5Hr		
Charger	On-board 15amp DC output at 48V				AC 3Ø 220V/380V, 50Hz
Control System	Solid state continuously variable controller, 350amp				FET Control Type
Tire	Type	Pneumatic Tire			
	Front Wheel	800/824			
	Rear Wheel	800/824			

※The above specifications are subject to change without prior notice.

