

SST-4000/ 6000 / 8000

Total Moving System SOOSUNG



■ SST-4000 (3-wheel)

- Suitable for large volumes and various types of cargo transportation.
- Suitable for trailer, bulky and heavy cargo (load) as well
- Easy operation, even for the inexperienced operator.
- Electrically powered cart, using a DC motor, enables the users to enjoy a non-polluting, noise free and pleasant working condition.



■ SST-8000 (4-wheel)

AC Type is optional

Specifications

Model		Unit	SST-4000 (3Wheel)	SST-6000 (3Wheel)	SST-8000 (4Wheel)
Towing Load		kg	4000	6000	8000
Towing Power		kg	100	150	200
Hook Height		mm	300	300	350
Overall Length		mm	2081	2081	2220
Overall Width		mm	1100	1100	1100
Overall Height		mm	1390	1390	1490
Weight		kg	1130	1130	2200
Wheel Base		mm	1198	1198	1250
Turning Radius		mm	1550	1550	2018
Travel speed	With Load	km/hr	6	6	8
	Without Load	km/hr	10	10	12
Driving Motor		kw	4	4	5
Battery	Capacity		DC48V × 201Ah/5Hr	DC48V × 320Ah/5Hr	DC48V × 400Ah/5Hr
Battery	Power		AC3φ × 220V, 50 or 60Hz	AC3φ × 220V, 50 or 60Hz	AC3φ × 380V, 50 or 60Hz
Control System			F,E,T Control Type	F,E,T Control Type	F,E,T Control Type
Tire	Type		Solid Tire	Solid Tire	R : Pneumatic F : Solid
	Front	(no.)	φ 343 × 140(1)	φ 343 × 140(1)	5,00-8 (2)
	Rear	(no, x=driven)	4,00-8 (2)	4,00-8 (2)	6,50-8 (2x)

※ The above specifications are subject to change without prior notice.

※ Option added, Price and Delivery will be changed.

